



DP63FC - 1C - 12VDC

Relay Type:-

Contact Form:- 1C

Coil voltage :- DC:- 6~110V, AC:- 6~240V

Model		DP63FC			
Features	Dimension L * W * H (mm)	78.5 x 45.8 x 46			
	Terminal Type	Screw Terminal			
Contact Data	Contact Form	1C			
	Contact Material	Ag Alloy			
	Contact Capacity	63A 250VAC			
Coil Data	Coil Voltage (DC)	6 - 110 VDC			
	Coil Voltage (AC)	6 - 240 VAC			
	Coil Power Consumption	DC: 2.2W			
	Coil Specification	Coil Voltage	Coil Resistance (Ω) ±10%	Pull in Voltage	Drop Out Voltage
		12 VDC	65	80 %	5 %
24 VDC		252	80 %	5 %	
240 VAC		5200	85 %	30 %	
General Data	Dielectric Strength	1200 VAC @ 50 Hz / Min (Between Contacts)			
		2500 VAC @ 50 Hz / Min (Between Coil & Contacts)			
	Insulation Resistance	1000 MΩ , 500VDC			
	Operate time / Release time	30ms / 30ms			
Mounting Diagram					
Application	Inverter, Voltage stabilizer, High Power Application, Phase Changeovers, Motor Controller, Street Lighting, HVAC etc.				