



## Contact Rating

Contact Form	2C	4C
Contact Resistance	50mΩ (1A 6VDC)	
Contact Material	Silver alloy	
Contact Capacity	10A/250VAC 30VDC	3A,5A/250VAC 30VDC

## General Specification

Insulation Resistance	500MΩ, 500VDC
Dielectric Strength	1000VAC (Between Open Contact)
	1500VAC (Between Coil & Contact)
Operating Time	25ms/25ms
Operating Temperature	-40 ~ +60°C

## Coil Rating

Nominal Coil Power	0.9W, 1.2VA
Coil Voltage	5 ~ 110VDC, 6 ~ 240VAC

## Coil Data Chart

Nominal Voltage VDC	Pull in Voltage VDC	Release Voltage VDC	Coil Resistance Ω ±10%	Nominal Voltage VAC	Pull in Voltage VAC	Release Voltage VAC	Coil Resistance Ω ±10%
5	4.0	0.50	30	6	4.80	1.80	12
6	4.8	0.60	40	12	9.60	3.60	42
12	9.6	1.20	160	24	19.20	7.20	168
24	19.2	2.40	640	48	38.40	14.40	675
48	38.4	4.80	2560	120	96.00	36.00	3500
110	88.0	11.0	12100	220/240	176.00	66.00	14000/16500

## Dimension Bottom View

